



POLEMOUNT TYPE ONAN 60Hz 65°C

1 PH. 167 kVA	SERIAL No			
IMPEDANCE AT 85°C	%	VOL. OF OIL	L	
BIL	95X125 kV	TOTAL MASS	kg	
H.V.	7200/12470Y V X	14400/24940Y	V	
L.V.	120/240 V	< 2 PPM PCB		

DV	TAPS CHANGER (TC)				
POSITIONS	1	2	3	4	5
7.2 kV	105 %	102.5 %	100 %	97.5 %	95 %
14.4 kV	105 %	102.5 %	100 %	97.5 %	95 %

WARNING: OPERATE SWITCHES ONLY WHEN TRANSFORMER IS DE-ENERGIZED

ENERGY EFFICIENCY PER CAN/CSA C802.1

P.O. No. _____ DATE _____

BUILT TO CSA C2.2 | MFR. REF.No. TAO167DMA1HL002

ABB QUEBEC, CANADA R00

CUSTOMER APPROVAL

APPROVED:

APPROVED AS NOTED:

NOT APPROVED:

BY: _____

NOTES:

- MEET REQUIREMENTS OF APPLICABLE CSA C2.2-06 SPECIFICATION
- MARKING ACCORDING TO CSA C2.2-06 SPECIFICATION

FINISH:

- ACCORDING TO CSA C2.2-06 SPECIFICATION CLAUSE 8.10

CALCULATED VALUES	
% IZ :	2.3 %
OIL :	229 L
WEIGHT :	698 Kg

no. REVISIONS	date	DESCRIPTION	BY	APPR.
DRAWN.	P.A.B.	DATE: 2017/11/22	DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED 1LCA TAO167DMA1HL002	
ELEC.APP.	A.A.	DATE: 2017/11/22		
MEC.APP.	A.T.	DATE: 2017/11/22		
SCALE:	1=15			