



Technical Documentation

APH03065-841

Advantage Plus IEEE 841 | AEHH8B

Beaver Electrical Machinery Ltd.

Date: July 25, 2022



Dimensional Drawing

Catalogue	Type	HP	RPM	Voltage	Hz	Frame Size
APH03065-841	AEHH8B	30	1200	575	60	326T




FIG. 4



Mounting					A	B	C	CL1	CL2	D	G
E	2F1	2F2	H	BA							
6.25	12	10.5	0.66	5.25	15.75	14.37	31.43			8	1.1

J	K	L	M	O	P	T
3.15		14.93	10.85	16.22	16.55	2.36

Terminal Housing			
AA	AB	AC	XB
NPT2"	14.72	11.3	3.59

Shaft Extension			Key			Keyseat
N-W	U	V	Width	Thick	Length	R
5.25	2.125	5.15	0.5	0.5	3.91	1.845

Bearings		Weight Lbs	Drive Method	Dimensions
DE	NDE			
6312ZC3	6212ZC3	695	Direct Coupling / Belt Drive	Inches

	Beaver Electrical Machinery Ltd.	
	Date: July 25, 2022	

Technical Data Sheet

Motor Type: AEHH8B	Catalogue No: APH03065-841
--------------------	----------------------------

Nameplate Information

HP	Pole	RPM	Frame	Voltage	Hz	Phase
30	6	1175	326T	575	60	3
Enclosure	Ins. Class	Service Factor	Time Rating	NEMA Design	Rated Amb.	Rated Altitude
TEFC	F	1.15	Continuous	B	-40 to 40 °C	<1000 m

Typical Performance

Efficiency (%)				Power Factor (%)		
Full Load		3/4 Load	1/2 Load	Full Load	3/4 Load	1/2 Load
Nom.	Min.					
93	91.7	93.6	93.6	80.5	78.5	71
Torque				Current (A)		
Full Load (lb-ft)	Locked Rotor (% FLT)	Pull Up (% FLT)	Break Down (% FLT)	No Load	Full Load	Locked Rotor
134.1	210	180	230	9.3	30.0	174.4
NEMA KVA Code	Inertia (WR ²)			Safe Stall Time (s)		Noise Level Sound Press. dB(A)
	Rotor (lb-ft ²)	NEMA Load (lb-ft ²)	Max. Allowable (lb-ft ²)	Cold	Hot	
G	12.372	384	636	17	12	72

VFD Duty Information

Max HP	Current (A)	Speed Range		VFD		S.F.
		Constant Torque	Variable Torque	Carrier Hz	Type	
30	30.02	6-60Hz	3-60Hz	3-6kHz	VPWM or CPWM	1

Hazardous Locations Information



CSA Certified
Class I, Div 2, Groups B, C & D Class I, Zone 2, Groups IIB+H2, IIB & IIA
Temp Code (Sinewave / VFD)
T3C / T3B

Additional Certifications

Other Certification

Additional Information

Bearings		Approx. Weight
DE	NDE	lbs
6312ZC3	6212ZC3	695


	Beaver Electrical Machinery Ltd.	
	Date: July 25, 2022	

Nameplate Drawing

Advantage Plus IEEE 841					
TYPE	AEHH8B		CAT. NO.	APH03065-841	
OUTPUT	30 HP 22.38 kW		FRAME	326T	TEFC
R.P.M.	1175		POLE	6	INS. F
VOLTS	575		PHASE	3	Hz 60
AMPS	30.0		CODE	G	S.F. 1.15
AMBIENT	40 °C		NOM. EFF. 93		MIN. EFF. 91.7
BEARINGS	6312ZC3 / 6212ZC3				RATING Cont.
SER. NO.	TBD		DESIGN	B	WT. 695 LBS
PWM VFD DUTY	VT	CT	CP		S.F.
	3-60Hz	6-60Hz	60-120Hz		1



Connection Diagram




3 LEAD SINGLE VOLTAGE DELTA					
VOLTAGE	CONN.	L1	L2	L3	
-	DELTA	1	2	3	

WD_3D



Thermal Limit Curves

Motor Type: AEHH8B		Catalogue No: APH03065-841		Family: Advantage Plus IEEE 841	
HP	30	Safe Stall Time		Full Load A	30.0 A
Voltage	575V 60Hz	Hot	12 s	% Inrush	581 %
RPM	1200	Cold	17 s	Locked Rotor A	174.4 A





T-N and I-N Curves

Motor Type: AEHH8B		Catalogue No: APH03065-841		Family: Advantage Plus IEEE 841	
HP	30	Full Load T	134.1 lb-ft	Full Load A	30.0 A
Voltage	575V 60Hz	Locked Rotor T	210 %	Locked Rotor A	174.4 A
RPM	1200	Pull Up T	180 %	Break Down T	230 %

