




BEAVER ELECTRICAL MACHINERY
7440 LOWLAND DRIVE, BURNABY, BC, CANADA
TEL: (604) 431-5000 FAX: (604) 431-5066
www.beaverelectrical.com

SVR SERIES SPECIFICATION SHEET

1 PHASE ISOLATION TRANSFORMER TYPE: DRY TYPE


CAT. NO.: SVR10H-G8C
KVA: 10
PRIMARY VOLT: 208
SECONDARY VOLT: 120/240
PHASE: 1
FREQ: 60 HZ
WEIGHT: 110 LBS
INSUL. CLASS: 220°C
TEMP. RISE: 150°C
BIL: 10 KV
IMPEDANCE: 5.0 - 6.0%
WINDING: Copper
ENCLOSURE: NEMA Type 1
NEMA Type 3R with optional kit
APPROVALS: UL, CSA

OUTLINE DRAWING



WIRING AND CONNECTION DIAGRAM

HI VOLT	% TAPS	JUMPERS TO	LOW VOLT	INTERCONNECT	SEC LINE CONN
218	105.0	1-1	240	X2 TO X3	X1 - X4
213	102.5	2-2	120/240	X2 TO X3	X1 - X2 - X4 (X2 IS A NEUTRAL)
208	100.0	3-3			
203	97.5	4-4	120	X1 TO X3 AND X2 TO X4	X1-X4
198	95.0	5-5			



NOTE: Specifications and dimensions subject to change without notice