




BEAVER ELECTRICAL MACHINERY
7440 LOWLAND DRIVE, BURNABY, BC, CANADA
TEL: (604) 431-5000 FAX: (604) 431-5066
www.beaverelectrical.com

TVR SERIES SPECIFICATION SHEET

3 PHASE TRANSFORMER TYPE: DRY TYPE FLOOR OR WALL MOUNT


CAT. NO.: TVR10T-Q34C
KVA: 10
PRIMARY VOLT: 600 ▲
SECONDARY VOLT: 400Y/230
PHASE: 3
FREQ: 60 HZ
WINDING MATL: Copper
WEIGHT: 143 LBS
INSUL. CLASS: 220°C
TEMP. RISE: 150°C
IMPEDANCE: 5.0-6.0%
TAPS: FULL CURRENT
BIL: 10 kV
ENCLOSURE: TYPE 2
TYPE 3R with optional kit
APPROVALS: UL, CSA

OUTLINE DRAWING



WIRING AND CONNECTION DIAGRAM

PRI VOLT	JUMPERS TO	PRI LINE CONN	SEC VOLT	PHASE	SEC LINE CONN
630	1-1-1	H1, H2, H3	400	3	X1, X2, X3
600	2-2-2	H1, H2, H3	230	1	BETWEEN X0 AND X1 or X2 or X3
570	3-3-3	H1, H2, H3			



NOTE: Specifications and dimensions subject to change without notice