




BEAVER ELECTRICAL MACHINERY
 7440 LOWLAND DRIVE, BURNABY, BC, CANADA
 TEL: (604) 431-5000 FAX: (604) 431-5066
 www.beavelectrical.com

TVR SERIES SPECIFICATION SHEET


3 PHASE TRANSFORMER DRY TYPE FLOOR MOUNT

CAT. NO.: TVR150H-S34A3
 KVA: 150
 PRIMARY VOLT: 208 ▲
 SECONDARY VOLT: 480Y/277
 PHASE: 3
 FREQ: 60 HZ
 WINDING MATL: ALUMINUM
 WEIGHT: 940 LBS
 INSUL. CLASS: 220°C
 TEMP. RISE: 150°C
 IMPEDANCE: 4.5-5.5%
 TAPS: SEE BELOW
 BIL: 10 kV
 ENCLOSURE: NEMA 1
 NEMA 3R with optional kit
 EFF. STANDARDS: NRCAN 2019, DOE 2016
 APPROVALS: UL, CSA



WIRING AND CONNECTION DIAGRAM

PRI VOLT	JUMPERS TO	PRI LINE CONN	SEC VOLT	PHASE	SEC LINE CONN
218	1-1-1	H1, H2, H3	480	3	X1, X2, X3
208	2-2-2	H1, H2, H3	277	1	BETWEEN X0 AND X1 or X2 or X2
198	3-3-3	H1, H2, H3			



NOTE: Specifications and dimensions subject to change without notice