




BEAVER ELECTRICAL MACHINERY
 7440 LOWLAND DRIVE, BURNABY, BC, CANADA
 TEL: (604) 431-5000 FAX: (604) 431-5066
 www.beaverelectrical.com

**TVR SERIES
 SPECIFICATION SHEET**


**3 PHASE TRANSFORMER
 TYPE: DRY TYPE
 FLOOR MOUNT**

CAT. NO.: TVR225T-K34A
 KVA: 225
 PRIMARY VOLT: 600▲
 SECONDARY VOLT: 240Y/139
 PHASE: 3
 FREQ: 60 HZ
 WINDING MATL: Aluminum
 WEIGHT: 1640 LBS
 INSUL. CLASS: 220°C
 TEMP. RISE: 150°C
 IMPEDANCE: ~5.0%
 Eff. @ 35% load: 98.5%
 BIL: 10 kV
 ENCLOSURE: TYPE 2
 NEMA 3R with optional kit
 APPROVALS: UL, CSA



CONNECTION AND TAP INFORMATION

PRI VOLT	INTERCONNECT	PRI LINE CONN	SEC VOLT	PHASE	SEC LINE CONN
630	1-2	H1, H2, H3	240	3	X1, X2, X3
615	2-3	H1, H2, H3	139	1	BETWEEN X0 AND X1 or X2 or X3
600	3-4	H1, H2, H3			
585	4-5	H1, H2, H3			
570	5-6	H1, H2, H3			



NOTE: Specifications and dimensions subject to change without notice