




BEAVER ELECTRICAL MACHINERY
 7440 LOWLAND DRIVE, BURNABY, BC, CANADA
 TEL: (604) 431-5000 FAX: (604) 431-5066
 www.beverelectrical.com

**TVR SERIES
 SPECIFICATION SHEET**

**3 PHASE TRANSFORMER
 TYPE: DRY TYPE
 FLOOR MOUNT**



CAT. NO.: TVR500S-T34A3
 KVA: 500
 PRIMARY VOLT: 480 ▲
 SECONDARY VOLT: 600Y/347
 PHASE: 3
 FREQ: 60 HZ
 WINDING MATL: Aluminum
 WEIGHT: 2950 LBS
 INSUL. CLASS: 220°C
 TEMP. RISE: 150°C
 IMPEDANCE: 5.5%
 TAPS: SEE BELOW
 BIL: 10 kV
 ENCLOSURE: NEMA 2
 NEMA 3R with optional kit
 APPROVALS: UL, CSA

OUTLINE DRAWING



CONNECTION AND TAP INFORMATION

PRI VOLT	INTERCONNECT	PRI LINE CONN	SEC VOLT	PHASE	SEC LINE CONN
504	1-2	H1, H2, H3	600	3	X1, X2, X3
492	2-3	H1, H2, H3	347	1	BETWEEN X0 AND X1 or X2 or X2
480	3-4	H1, H2, H3			
468	4-5	H1, H2, H3			
456	5-6	H1, H2, H3			



NOTE: Specifications and dimensions subject to change without notice